

5Y85 5Y89

BSB0005C-A0609

セイコーウォッチ株式会社 <http://www.seiko-watch.co.jp/>

お客様相談窓口(全国フリーダイヤル)0120-612-911(下記の最寄地に着信いたします)

お客様相談室

東京 〒101-0044 東京都千代田区鍛冶町 2-1-10

大阪 〒550-0013 大阪市西区新町 1-4-24 大阪四ツ橋新町ビルディング 8階

# SEIKO

## 取扱説明書

### I N S T R U C T I O N S

# P

この度は弊社製品をお買い上げいただき、  
誠にありがとうございました。  
ご使用前にこの説明書をよくお読みの上  
正しくご愛用くださいますよう、お願い申し上げます。  
なお、この説明書はお手元に保管し必要に応じてご覧ください。

※ お買い求めの際の金属バンドの調整は  
お買い上げ店・弊社お客様相談窓口  
(裏表紙に記載)にて承っておりますが、  
その他のお店では有料もしくはお取扱い  
いただけない場合があります。

※ 保証期間内でも電池交換は  
有料となります。  
お買い上げの時計には検査用のモニター  
電池が入っています。所定の年数よりも  
早めに電池が切れることがあります。



## 警告

取扱いを誤った場合に、重傷を負うなどの重大な結果になる危険性が想定されることを示します。



**時計から電池を取り出さないでください**



**乳幼児の手の届くところに時計本体や部品を置かないでください**

電池や部品を乳幼児が飲み込んでしまうおそれがあります。万一飲み込んだ場合は、身体に害があるため、ただちに医師とご相談ください。



**次のような場合、ご使用を中止してください**

- 時計本体やバンドが腐食等により鋭利になった場合
- バンドのピンが飛び出してきた場合

※ すぐにお買い上げ店・弊社お客様相談窓口（裏表紙に記載）にご相談ください



## 注意

取扱いを誤った場合に、軽傷を負う危険性や物質的損害をこうむることが想定されることを示します。



**以下の場所での携帯・保管は避けてください**

- 揮発性の薬品が発散しているところ（除光液などの化粧品・防虫剤・シンナーなど）
  - 5℃～35℃から外れる温度に長期間なるところ ○ 高湿度なところ
  - 磁気や静電気の影響があるところ ○ ホコリの多いところ ○ 強い振動のあるところ
- ※ 電池が切れた状態で長時間放置しないでください。電池が漏液するおそれがあります。



**アレルギーやかぶれを起こした場合**

ただちに時計の使用をやめ、皮膚科など専門医に相談してください。



**その他のご注意**

- 上げ時計やペンダント時計のひもやチェーンが衣類や手・首などを傷つけるおそれがありますのでご注意ください。
- 商品の分解・改造はしないでください。
- 乳幼児に時計が触れないようにご注意ください。ケガやアレルギーをひき起こすおそれがあります。

## CONTENTS [目次]

### 操作について

各部の名称	6
時刻の合わせ方	8
曜日の合わせ方	9
日付の合わせ方	10

### ご注意いただきたいこと


アフターサービスについて	14
保証について	16
お手入れについて	18
防水性能について	20
耐磁性能について	24
バンドについて	26
特殊な中留の使い方について	28
使用電池・電池寿命・精度について	34

## 操作について

## 各部の名称



## りゅうずをご確認ください



※ りゅうずが誤って引き出される事を防止するため、時計本体にねじ止めできるりゅうずです。

- 時計の操作後は必ずりゅうずを押し付けながら右に回して元通りに締めてください。
- りゅうずを締める時、回しにくい場合は元に戻してからやり直してください。
- 無理に締めますとねじを壊す恐れがあります。

## 時刻の合わせ方

分針が12時の位置で、りゅうずを2段目まで引き出します。






りゅうずを回して時刻を合わせます。

正確に合わせるために分針を正しい時刻より4～5分進めてから逆に戻して合わせてください。



時報と同時にりゅうずを押し込みます。



※24時針は時針に連動して動きます。単独での修正はできません。

## 曜日の合わせ方 (午後9時～午前1時の間には行わないでください。)

曜針は24時間に1回動きます。修正を行う時は、時針・分針を進めて合わせます。

- りゅうずを2段目まで引き出します。
- りゅうずを右に回して時針・分針を進めます。午前0時を過ぎると曜針が動き始めますので、次の曜日を曜針が示すまで時針・分針を動かしてください。
- 曜針をさらに進める場合は、時針・分針を逆に4～5時間戻し、その後時針・分針を進めて再び午前0時を通過させると曜針を早く進めることができます。これを繰り返して曜日を合わせてください。
- 曜日を合わせた後は、時刻合わせを行ってください。

### ご注意

ねじロック式りゅうずのモデルは、必ずりゅうずを元通りに締めてください。

### ご注意

りゅうずの回転は静かに行ってください。

## 日付の合わせ方 (午後9時～午前1時の間には行わないでください。)




リューズを1段  
引き出します。



リューズを右に  
回して日付を合  
合わせます。



リューズを  
押し込みます。



### ご注意

ねじロック式リューズのモデルは、必ずリューズを元通りに締めてください。

## 日付の修正が必要な場合

日付は31日周期で切り替わります。  
1か月が31日に満たない月の翌月は日付を修正してください。

### ご注意

#### 日付(曜日)の修正をしてはいけない時間帯

午後9時～午前1時  
(日付(曜日)が変わらないことがあります。)

#### 日中に日付(曜日)が切り替わる場合

午前と午後が合っていません。  
時刻を12時間進めてください。  
(「時刻の合わせ方」をご覧ください。)

ご注意いただきたいこと

## アフターサービスについて

### 修理用部品について

- この時計の修理用部品の保有期間は通常7年間を基準としています。
- 修理の際、一部代替部品を使用させていただくことがありますのでご了承ください。

### 電池交換について

- 秒針が2秒おきに動くようになったら、電池が切れる合図です。
- 電池交換はお買い上げ店・弊社お客様相談窓口にご依頼ください。その際パッキン交換をご依頼ください。
- 電池交換は保証期間内でも有料となります。
- 10気圧防水以上の時計は、防水検査をご依頼ください。防水検査は日数を要しますので期間をご確認ください。
- 電池交換してもすぐ止る場合はオーバーホールが必要です。

### オーバーホール(分解掃除)について

時計は精密機械です。部品の油切れや磨耗により止まり遅れが生じることがあります。その際にはオーバーホールをご依頼ください。オーバーホールの際にはパッキンやバネ棒の交換もご依頼ください。

### 保証と修理について

- 修理やオーバーホールの際は、お買い上げ店・弊社お客様相談窓口にご相談ください。
- 保証期間内の場合は必ず保証書を添えてください。
- 保証内容は保証書に記載したとおりです。よくお読みいただき大切に保管してください。

## 保証について

取扱説明書にそった正常な使用により、お買い上げ後1年以内に、不具合が生じた場合には、下記の保証規定によって無料で修理・調整いたします。

### 保証の対象部分

- 時計本体(ムーブメント・ケース)及び金属バンドです。

保証の適用除外(保証期間内あるいは保証対象部分であっても、次のような場合には有料になります)

- 電池交換及び皮革・ウレタン・布等のバンドの交換
- 事故または不適切な取扱いによって生じた故障および損傷
- ご使用中に生じるキズ・汚れ等
- 火災・水害・地震等の天災地変による故障及び損傷
- 保証書記載項目の全てが記入された保証書のみが有効です。故意に字句を書き換えた場合は規定の無償修理は受けられません。

保証は、保証書に明示した期間・条件のもとにおいて、無料修理をお約束するものです。これによりお客様の法律上の権利を制限するものではありません。保証書は日本国内のみ有効です。

### 保証を受ける手続き

- 保証対象の不具合が生じた場合は、時計と別紙保証書をご持参の上、お買い上げ店にご依頼ください。
- お買い上げ店の保証が受けられない場合には、「セイコーウオッチ株式会社 お客様相談窓口」に保証書を添えてご依頼ください。

### その他

- 修理の際、ムーブメントを交換させていただいたり、ケース・文字板・針・ガラス・バンド等に一部代替部品を使用させていただくこともありますので、ご了承ください。ご使用部品の保有期間は本取扱説明書(P.14)をご参照ください。
- 金属バンド等の調整は、お買い上げ店または弊社お客様相談窓口にご依頼ください。上記以外の販売店での調整は有料になります。

## お手入れについて


### 日頃からこまめにお手入れしてください

- 水分や汗、汚れはこまめに柔らかい布で拭き取るように心掛けてください。
- すきま（金属バンド、りゅうず周り、裏ぶた周りなど）の汚れは柔らかい歯ブラシが有効です。
- 海水に浸けた後は、必ず真水でよく洗ってから拭き取ってください。
- その際、直接蛇口から水をかけることは避け、容器に水をためるなどしてから洗ってください。

### りゅうずは時々回してください

- りゅうずの錆び付きを防止するために、時々りゅうずを回してください。
- ねじロック式りゅうずの場合も同様です。（りゅうずを引く必要はありません）

## 時計の裏ぶたでも性能と型式の確認ができます



※上記の図は例であり、お買い上げいただいた時計とは異なります。

## 防水性能について

お買い上げいただいた時計の防水性能を  
下記の表でご確認の上で使用ください。  
(「P.19」をご覧ください)

裏ぶた表示	防水性能
表示なし	非防水です。
WATER RESISTANT	日常生活用防水です。
WATER RESISTANT 5 BAR	日常生活用強化防水で5気圧防水です。
WATER RESISTANT 10 (20) BAR	日常生活用強化防水で10(20)気圧防水です。



**注意**

- 防水性能を維持するため、電池交換の際は必ずパッキン交換をご依頼ください。
- また電池交換の際、10気圧防水以上の時計は防水検査をご依頼ください。

### お取扱方法

水滴がかかったり、汗を多くかく場合には、使用しないで下さい。

日常生活での「水がかかる」程度の環境であれば使用できます。



**警告**

水泳には使用しないで下さい。

水泳などのスポーツに使用できます。

空気ボンベを使用しないスキンドайビングに使用できます。

**警告**



この時計はスキューバダイビングや飽和潜水には絶対に使用しないで下さい

BAR (気圧) 表示防水時計はスキューバダイビングや飽和潜水用の時計に必要なとされる苛酷な環境を想定した様々な厳しい検査を行っていません。専用のダイバースウォッチをご使用下さい。

**注意**

※ 万一、ガラス内面にくもりや水滴が発生し、長時間消えない場合は防水不良です。お早めに、お買い上げ店・弊社お客様相談窓口(裏表紙に記載)にご相談ください。



水分のついたまま、りゅうずやボタンを操作しないで下さい

時計内部に水分が入ることがあります。

**注意**



水や汗、汚れが付着したままにしておくのは避けて下さい

防水時計でもガラスの接着面・パッキンの劣化や、ステンレスが錆びることにより、防水不良になる恐れがあります。



入浴やサウナの際はご使用を避けてください

蒸気や石けん、温泉の成分などが防水性能の劣化を早めてしまうからです。



直接蛇口から水をかけることは避けてください

水道水は非常に水圧が高く、日常生活用強化防水の時計でも防水不良になる恐れがあります。

**耐磁性能について (磁気の影響)**

アナログクォーツ時計は、身近にある磁気の影響を受け、時刻が狂ったり止まったりします。

※ 磁気により時刻が狂っても、遠ざければ正常に動きます。時刻を合わせ直してお使いください。

裏がた表示	お取扱方法
表示なし	磁気製品より10cm以上遠ざける必要があります。
	磁気製品に5cm以上遠ざける必要があります。 (JIS水準1種)
	磁気製品に1cm以上遠ざける必要があります。 (JIS水準2種)

**時計に影響を及ぼす身の周りの磁気製品例**



携帯電話 (スピーカー部)

磁気健康バンド



バッグ (磁石の止め金)

磁気ネックレス



交流電気かみそり

磁気健康マット



携帯ラジオ (スピーカー部)

磁気健康枕

電磁調理器

など

**アナログクォーツ時計が磁気の影響を受ける理由**

内蔵されているモーターは磁石を使用しており、外からの強い磁力で互いに影響し合い、モーターを止めたり、無理に回転させてしまうためです。

## バンドについて

バンドは直接肌に触れ、汗やほこりで汚れます。そのため、手入れが悪いとバンドが早く傷んだり、肌のかぶれ・そで口の汚れなどの原因になります。長くお使いになるためには、こまめなお手入れが必要です。

### 金属バンド

- ステンレスバンドも水・汗・汚れをそのままにしておくとさび易くなります。
- 手入れが悪いとかぶれやワイシャツの袖口が黄色や金色に汚れる原因になります。
- 水や汗・汚れは、早めに柔らかな布で取り除いてください。
- バンドのすき間の汚れは、水で洗い、柔らかな歯ブラシ等で取り除いてください。(時計本体は水にぬれないように台所用ラップなどで保護しておきましょう)

### 皮革バンド

- 水や汗、直射日光には弱く、色落ちや劣化の原因になります。
- 水がかかった時や汗をかいた後は、すぐに乾いた布などで吸い取るように軽く拭いてください。
- 直接日光にあたる場所に放置しないでください。
- 色味の薄いバンドは、汚れが目立ちやすいので、ご使用の際はご注意ください。

- 時計本体が日常生活強化防水(10気圧防水)になっているものでも、アクアフリーバンド以外の皮革バンドは、入浴中や水泳、水仕事などでのご使用はお控えください。

### ポリウレタンバンド

- 光で色が褪せたり、溶剤や空気中の湿気などにより劣化する性質があります。
- 特に半透明や、白色、淡色のバンドは、他の色を吸着し易く、また変色をおこします。
- 汚れたら水で洗い、乾いた布で良く拭き取ってください。(時計本体は水にぬれないように台所用ラップなどで保護しておきましょう)
- 弾力性がなくなり、ひび割れを生じたら取り替え時期です。

### かぶれやアレルギーについて

バンドによるかぶれは、金属や皮革が原因となるアレルギー反応や、汚れもしくはバンドとのすれなど不快感が原因となる場合など、いろいろな発生原因があります。

### バンドサイズの目安について


バンドは多少余裕をもたせ通気性をよくしてご使用ください。時計をつけた状態で、指一本入る程度が適当です。




## 特殊な中留の使い方について

皮革バンド、および、メタルバンドの一部に特殊な中留を用いたものがございます。お買い上げの時計の中留が下記のいずれかに当てはまる場合は、各々の操作方法をご覧ください。

- A 三ツ折中留 (皮革バンド専用)    
 B ワンプッシュ三ツ折中留 (皮革バンド、メタルバンド)





③ ワンプッシュ三ツ折中留 (皮革バンド専用)





## A 三ツ折中留 (皮革バンド専用) の使い方

- 1) バンドを定革、遊革から抜いて、中留を開きます。
- 3) ピンをバンドの調整穴から外し、バンドを左右にスライドさせて適切な長さのところでピンを調整穴にもう一度入れます。



- 2) 上箱の底板を下に開きます。
- 4) 底板を閉めます。(底板を押し込みすぎないようにしてください。)





※中留を装着するときは、バンドの剣先(先端)を定・遊革に入れてから、中留をしっかり留めて下さい。



## B ワンプッシュミツ折中留 (皮革バンド、メタルバンド) の使い方

### ① 時計の着脱方法



- 1) 両方のプッシュボタンを押しながらバンドを定革・遊革から抜いて、中留を開きます。
- 2) バンドの剣先 (先端) を定革・遊革に入れてから、上箱の上面位置をしっかりと押さえ留めます。



※メタルバンドの場合は、定革がない場合がございます。



### ② バンドの長さ調整方法

- 1) 両方のプッシュボタンを押しながらバンドを定革・遊革から抜いて、中留を開きます。
- 2) もう一度プッシュボタンを押し上箱を下に開きます。




## C ワンプッシュミツ折中留 (皮革バンド専用) の使い方


- 3) ピンをバンドのアジャスト穴から外し、バンドを左右にスライドさせて適切な長さのところでピンをアジャスト穴に入れます。
- 4) プッシュボタンを押しながら上箱を開めます。



- 1) プッシュボタンを押しながら中留を開きます。



- 2) バンドのアジャスト穴をピンから外し、バンドを左右にスライドさせて適切な長さのところでピンをアジャスト穴にもう一度入れプッシュボタンを押しながら中留をしっかりと抑え留めます。



## 使用電池・電池寿命・精度について

機種は裏ぶたでご確認いただけます。  
(「お手入れについて」をご覧ください)

機種	型式番号の前4桁 (例:5Y85-0AG0)	使用電池 SB-	電池 寿命	精度 (平均 偏差)
5Y85 5Y89		AJ	約3年	±15秒

- 上記の電池寿命は新しく電池を入れたときのものです。
- お買い上げ時の電池は検査用のモニター電池ですので、上記期間より早く切れる事があります。
- 精度は常温(5℃～35℃)において腕につけた場合のものです。
- 作動温度範囲は-5℃～+50℃です。

Thank you very much for choosing a SEIKO watch.  
For proper and safe use of your SEIKO watch,  
please read carefully the instructions  
in this booklet before using.

Keep this manual handy for easy reference.

※Length adjustment service for metallic bands is available at the retailer from whom the watch was purchased or SEIKO CUSTOMER SERVICE CENTER (listed on the back cover). The service may also be available on a chargeable basis at other retailers, however, some retailers may not undertake the service.

※Battery replacement is at cost even within the guarantee period.

The battery in the watch at the time of purchase is a monitor battery inserted in the watch at the factory for performance checks. Therefore, the battery may run down earlier than the specified period.

### WARNING

To indicate the risks of serious consequences such as severe injuries unless the following safety regulations are strictly observed.



**Do not remove the battery from the watch.**



**Keep the watch and accessories out of the reach of babies and children.**

Care should be taken to prevent a baby or a child accidentally swallowing the battery or accessories.  
If a baby or child swallows the battery or accessories, immediately consult a doctor, as it will be harmful to the health of the baby or child.



**Immediately stop wearing the watch in following cases.**

- If the watch body or band becomes edged by corrosion etc.
- If the pins protrude from the band.

※Immediately consult the retailer from whom the watch was purchased or SEIKO CUSTOMER SERVICE CENTER (listed on the back cover).

### CAUTIONS

To indicate the risks of light injuries or material damages unless the following safety regulations are strictly observed.



**Avoid the following places for wearing or keeping the watch.**

- Places where volatile agents (cosmetics such as polish remover, bug repellent, thinners etc.) are vaporizing
- Places where the temperature drops below 5 °C or rises above 35 °C for a long time
- Places of high humidity
- Places affected by strong magnetism or static electricity
- Dusty places ○ Places affected by strong vibrations

※ Do not leave a dead battery within the watch for a long time as leakage might occur.



**If you observe any allergic symptoms or skin irritation**

Stop wearing the watch immediately and consult a specialist such as a dermatologist or an allergist



**Other cautions**

- Note that there is a risk of damaging your clothes, hand or neck with the band, cord or chain of the pocket watch or pendant watch.
- Do not disassemble or tamper with the watch.
- Keep the watch out of the reach of babies and children. Extra care should be taken to avoid risks of any injury or allergic rash or itching that may be caused when they touch the watch.

# CONTENTS

## HOW TO USE

Names of the parts	44
Time setting	46
Day setting	47
Date setting	48

## TO PRESERVE THE QUALITY OF YOUR WATCH


After-sale service	52
Guarantee	54
Daily care	56
Water resistance	58
Magnetic resistance	62
Band	64
Special Clasps	66
Battery/Battery life/Accuracy	72

## HOW TO USE

## Names of the parts



## Check the type of the crown of your watch



- ※ This type of crown can be screwed into the watch body to avoid being pulled out by mistake.
- After completing all settings of the watch, screw the crown in again by turning it clockwise while pressing it.
  - If the crown turns out to be too stiff to be screwed up, turn the crown counterclockwise once and then give another try. Do not screw it in by force as it may damage the slots of the crown.

## Time setting

Pull out the crown to the second click when the second hand is at the 12 o'clock position.






Turn the crown to set the time.

In order to set the time accurately, turn the minute hand 4 to 5 minutes ahead and then return it to the correct time.



Push the crown back in to its normal position simultaneously with a time signal.



**Note** For models with a screw lock type crown, always screw the crown up again after setting the time

42  The telephone time signal service (Tel. 117) is convenient for setting the time.

## Day setting (Do not set day of the week between 9:00 PM and 1:00AM)

**The day hand cannot be adjusted independently of the other hands. Before setting the time, set the day by turning the hour and minute hands.**

- Pull out the crown all the way to the second click.
- Turn the crown clockwise to advance the hour and minute hands. When the hour and minute hands turn past the 12 o'clock marker, the day hand starts moving. Keep advancing the hour and minute hands until the day hand is set to the next.
- To advance the day hand quickly, turn back the hour and minute hands 4 to 5 hours after the day changes to the next, and then advance them again until the day hand is set to the next. Repeat the procedure above until the day hand is set to the desired day.
- After setting the day, set the time. When setting the hour hand, check that the 24-hour hand is correctly set.

**Note** When adjusting the day hand, turn the crown slowly.

## Date setting (Do not set date between 9:00 PM and 1:00 AM)




Pull out the crown to the first click.



Turn the crown to set the date.



Push the crown back in to its normal position.



**Note** For models with a screw lock type crown, always screw the crown up again after setting the time

### When date adjustment is required

The date makes one round in a 31-day period. It is necessary to adjust the date at the end of the month following a month that has less than 31 days.

#### Note

Time period that is not good for setting the date (day of the week)

Between 9:00 PM and 1:00 AM  
(The date (day of the week) may not change.)

When date (day of the week) changes during daytime

It happens when AM/PM is wrongly set. Advance the hour hand by twelve hours.  
(Refer to "Time Setting".)

## TO PRESERVE THE QUALITY OF YOUR WATCH

### After-sale service

#### Repair parts

- The repair parts of this watch will be retained usually for 7 years.
- Some alternative parts may be used for repair if necessary.

#### Battery replacement

- Contact the retailer from whom the watch was purchased or SEIKO CUSTOMER SERVICE CENTER to have the battery replaced with a new one. It is recommended to exchange the gasket at the same time to maintain the water resistant performance.
- Battery replacement will be at cost even within the guarantee period.
- For a water resistant watch with 10 BAR or above, a water resistant performance check is also recommended. Please note that it may take some days to conduct the check.
- If the watch runs down on a new battery, it requires an overhaul.

#### Notes on overhaul

The watch is a precision device. If the parts run short of the oil or get worn out, the watch may stop its operation or lose time. In such a case, have the watch overhauled. Be sure to have the gasket and push-pin replaced with new ones when overhauling the watch.

#### Notes on guarantee and repair

- Contact the retailer the watch was purchased from or SEIKO CUSTOMER SERVICE CENTER for repair or overhaul.
- Within the guarantee period, present the certificate of guarantee to receive repair services.
- Guarantee coverage is provided in the certificate of guarantee. Read carefully and retain it.

## Guarantee

Within one year from the date of purchase, we guarantee free repair/adjustment service against any defects according to the following guarantee regulations, provided that the watch was properly used as directed in this instruction booklet.

### Guarantee coverage

- The watch body (movement·case) and metallic band.

### Exceptions from guarantee

In following cases, repair/adjustment services will be at cost even within the guarantee period or under guarantee coverage.

- Battery replacement and change of leather/urethane/cloth band
- Troubles or damage caused by accidents or improper usage
- Scratches or grime caused by use
- Problems and damage caused by acts of god, natural disasters including fire, floods or earthquakes.
- The certificate of guarantee is valid only if all the necessary items are properly filled in. We will not honor an altered or tampered certificate of guarantee for free repair services.

50

## Daily care

### The watch requires good daily care

- Wipe away moisture, sweat or dirt with a soft cloth
- To clean the clearances (around the metallic band, crown or case back), a soft toothbrush is convenient.
- After soaking the watch in seawater, be sure to wash the watch in clean pure water and wipe it dry carefully.

### Turn the crown from time to time

- In order to prevent corrosion of the crown, turn the crown from time to time.
- The same practice should be applied to a screw lock type crown. (No need to pull out the screw lock type crown.)

52

Free repair services are guaranteed only under the period and conditions specified in the certificate of guarantee. It does not affect specific legal rights of a consumer.

The certificate of guarantee is valid only in Japan.

### Procedure to claim free repair services


- For any defects under guarantee, submit the watch together with the attached certificate of guarantee to the retailer from whom the watch was purchased.
- If repair services cannot be provided by the retailer from whom the watch was purchased, contact SEIKO CUSTOMER SERVICE CENTER. In this case, the attached certificate of guarantee is also needed.

### Others

- The case, dial, hands, glass and bracelet, or parts thereof may be repaired with substitutes if the originals are not available. If necessary, movements will be replaced. Refer to the page 52 of this booklet for the retention period of the parts.
- For length adjustment service of a metallic band, ask the retailer from whom the watch was purchased or SEIKO CUSTOMER SERVICE CENTER. Other retailers may undertake the service on a chargeable basis.

51

### The case back shows the caliber and performance of your watch



※The figure above is one example. Performance of your watch is different from above sample.

53

# Water Resistance

Refer the table below for the description of each degree of water resistant performance of your watch before using.

(Refer to ' P.57 ')

Indication on the case back	Water resistant performance
No indication	Non-water resistance
WATER RESISTANT	Water resistance for everyday life
WATER RESISTANT 5 BAR	Water resistance for everyday life at 5 barometric pressures
WATER RESISTANT 10 (20) BAR	Water resistance for everyday life at 10 (20) barometric pressures.

54

## ⚠ Cautions

- In order to maintain the water resistant performance at factory-adjusted level, make sure to replace the gasket when changing the battery.
- For a water resistant watch with 10 BAR or above, be sure to have the water resistant performance check when changing the battery.

## Condition of Use

**Avoid drops of water or sweat**

The watch withstands accidental contact with water in everyday life.

**⚠ WARNING** Not suitable for swimming

The watch is suitable for sports such as swimming.

The watch is suitable for diving not using an air cylinder.

55

## ⚠ WARNING



**Do not use the watch in scuba diving or saturation diving.**

The various tightened inspections under simulated harsh environment, which are usually required for watches designed for scuba diving or saturation diving, have not been conducted on the water-resistant watch with the BAR (barometric pressure) display. For diving, use special watches for diving.

## ⚠ CAUTION

- ※ If the inner surface of the glass is clouded with condensation or water droplets appear inside of the watch for a long time, the water resistant performance of the watch is deteriorated. Immediately consult the retailer from whom the watch was purchased or SEIKO CUSTOMER SERVICE CENTER (listed on the back cover).



**Do not turn or pull out the crown when the watch is wet.**

Water may get inside of the watch.

56

## ⚠ CAUTION



**Do not leave moisture, sweat and dirt on the watch for a long time.**

Be aware of a risk that a water resistant watch may lessen its water resistant performance because of deterioration of the adhesive on the glass or gasket, or the development of rust on stainless steel.



**Do not wear the watch while taking a bath or a sauna.**

Steam, soap or some components of a hot spring may accelerate the deterioration of water resistant performance of the watch.



**Do not pour running water directly from faucet.**

The water pressure of tap water from a faucet is high enough to degrade the water resistant performance of a water resistant watch for everyday life.



57

## Magnetic resistance (affect of magnetic field)

Affected by nearby magnetism,

a quartz watch may temporarily gain or lose time or stop operating.

※ This defective condition caused by magnetism will be corrected soon after the watch is removed from the magnetic source. Reset the time once again before using the watch.

Indication on the case back	Condition of use
No indication	Keep the watch more than 10 cm away from magnetic products.
	Keep the watch more than 5 cm away from magnetic products. (JIS level-1 standard)
	Keep the watch more than 1 cm away from magnetic products. (JIS level-2 standard)

## Examples of common magnetic products that may affect watches



Cellular phone (speaker)



Bag (with magnet buckle)

AC-powered shaver



Portable radio (speaker)



Magnetic cooking device etc

Magnetic health belt

Magnetic necklace

Magnetic health mat

Magnetic health pillow

The reason why analogue quartz watch is affected by magnetism.

It is because the built-in motor of the watch, which harnesses magnetic power and external strong magnetism, affect each other to stop the motor or suppresses the turn of the motor.

## Band (maintenance procedure)

The band touches the skin directly and becomes dirty with sweat or dust.

Therefore, lack of care may accelerate deterioration of the band or cause skin irritation or stain on the sleeve edge. The watch requires a lot of attention for long usage.

### Metallic band

- Moisture, sweat or soil will cause rust even on a stainless steel band if they are left for a long time.
- Lack of care may cause a yellowish or gold stain on the lower sleeve edge of shirts.
- Wipe off moisture, sweat or soil with a soft cloth as soon as possible
- To clean the soil around the joint gaps of the band, wipe it out in water and then brush it off with a soft toothbrush.  
(Protect the watch body from water splashes by wrapping it up in plastic wrap etc.)

### Leather band

- A leather band is susceptible to discoloration and deterioration from moisture, sweat and direct sunlight.
- Wipe off moisture and sweat as soon as possible by gently blotting them up with a dry cloth.
- Do not expose the watch to direct sunlight for a long time.
- Please take care when wearing a watch with light-colored band, as dirt is likely to show up.

- Refrain from wearing a leather band watch other than Aqua Free bands while bathing, swimming, and when working with water even if the watch itself is water-resistant enforced for daily use (10-BAR water resistant) .

### Polyurethane band

- A polyurethane band is susceptible to discoloration from light, and may be deteriorated by solvent or atmospheric humidity.
- Especially a translucent, white, or pale colored band easily adsorbs other colors, resulting in color smears or discoloration.
- Wash out dirt in water and clean it off with a dry cloth.  
(Protect the watch body from water splashes by wrapping it up in plastic wrap etc.)
- When the band becomes less flexible or cracked, replace the band with a new one.

### Notes on skin irritation and allergy

Skin irritation caused by a band has various reasons such as allergy to metals or leathers, or skin reactions against friction on dust or the band itself.

### Notes on the length of the band


Adjust the band to allow a little clearance with your wrist to ensure proper airflow. When wearing the watch, leave enough room to insert a finger between the band and your wrist.





## Special Clasps


There are 3 type of special clasps as described below;  
If the clasp of the watch you purchased is one of them,  
please refer to the indications.




62

## A Type


1) Lift up the clasp to release the buckle.




2) Open the flap.



3) Take the pin out of the adjustment hole, adjust the size of the strap by sliding it back and forth, and then put the pin back into the appropriate adjustment hole.



4) Close the flap.




63

## B Type

### 1 How to wear or take off the watch

- 1) Press the button on both sides of the buckle ; pull the buckle up.  
The band will automatically come out of the loop.
- 2) Place the tip of the band into the moveable loop and fixed loop, and fasten the clasp by pressing the frame of the buckle.




※No Fixed loop with Metal Bracelets.

64


### 2 How to adjust the length of the leather band

- 1) With pressing buttons on both sides of the buckle, pull the leather band out of the moveable loop and fixed loop. Then open the clasp.
- 2) Press the push buttons again to unfasten the buckle.




65


3) Pull the pin out of an adjustment hole of the band. Slide the band to adjust its length and find an appropriate hole. Place the pin into the hole.




4) Fasten the buckle with pressing the push buttons.



1) Press the button on the buckle, and lift to open the clasp.



2) To adjust : Pull the pins out of the adjustment holes on the band. Slide the band to the appropriate length. Push the pins into the new holes on the band.



## Battery/Battery life/Accuracy

Check the case back of your watch to identify the type of watch.  
(Refer to "Daily care".)

Type of watch (The first four digits of the caliber number of your watch Ex. 5Y85-0AG0)	Battery SB-	Battery life	Loss/Gain (per month)
5Y85 5Y89	AJ	Approx. 3 years	±15 seconds

- The battery life shown above is for a watch with a new battery.
- The battery in the watch at the time of purchase is a monitor battery inserted in the watch at the factory for performance checks, therefore, the battery may run down earlier than the above-specified period.
- The accuracy is under the condition that the watch is worn on the wrist in a normal temperature range between 5 °C and 35 °C.
- Operational temperature range : -5°C~+50°C